



ACTIVE NOISE CANCELING MICROPHONES

HM-209
HM-211

Amateur Radio

Land Mobile Radio



NOISE CANCELING MICROPHONES DELIVER OUTSTANDINGS IN EXTREME DUTIES



Less The Noise.


By mounting a superior DSP chip, HM-209/HM-211 can automatically* reduce noise in extremely noisy environments and assist in transmitting clear and accurate audio in both analog and digital modes. Whether around the engine, on the motor or near the wind noise, HM-209/HM-211 increases productivity by delivering effective communication in every extreme duty.

*No on/off/level switch

Audio Performance



Noise Canceling OFF



Noise Canceling ON
Image for illustration purposes only.

COMPATIBLE WITH:

- HM-209 : ID-880H, ID-E800, IC-2300H, ID-5100 A/E, IC-2730 A/E series
- HM-211 : IC-F5061/D, IC-F9511 T/S/HT, IC-F9521 T/S, IC-F5121D, IC-F6121D, IC-F5360D, IC-F6360D series

SPECIFICATIONS

- Power Supply Voltage : 8.0V (supplied by the main unit)
- Operating Temperature Range : HM-209 -10°C to +60°C
: HM-211 -30°C to +60°C
- Weight : HM-209 180g
: HM-211 220g
- Dimensions : W 65.0 × H 105.0 × D 35.0 mm
- Curly Cable Length : 300mm ± 30mm
- Connector : 8-pin modular

Check the audio comparison at:
http://www.icom.co.jp/r/e_HM-209/



Icom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries.